

Package: hms (via r-universe)

October 11, 2026

Title Pretty Time of Day
Date 2026-10-11
Version 1.1.4.9027
Description Implements an S3 class for storing and formatting
time-of-day values, based on the 'difftime' class.
License MIT + file LICENSE
URL <https://hms.tidyverse.org/>, <https://github.com/tidyverse/hms>
BugReports <https://github.com/tidyverse/hms/issues>
Imports cli, lifecycle, methods, pkgconfig, rlang (>= 1.0.2), vctrs
(>= 0.3.8)
Suggests crayon, lubridate, pillar (>= 1.1.0), testthat (>= 3.0.0),
tibble
Config/Needs/website tidyverse/tidytemplate
Config/testthat/edition 3
Encoding UTF-8
Roxygen list(markdown = TRUE)
Config/roxygen2/version 8.1.1.9000
Repository <https://cynkra.r-universe.dev>
Date/Publication 2026-10-11 00:31:05 UTC
RemoteUrl <https://github.com/tidyverse/hms>
RemoteRef HEAD
RemoteSha 1a68f847d07855509fe555261f9976a0a26f661a

Contents

hms	2
parse_hms	3
round_hms	4
vec_cast.hms	5
vec_ptype2.hms	5

hms

*A simple class for storing time-of-day values***Description**

The values are stored as a [difftime](#) vector with a custom class, and always with "seconds" as unit for robust coercion to numeric. Supports construction from time values, coercion to and from various data types, and formatting. Can be used as a regular column in a data frame.

`hms()` is a high-level constructor that accepts second, minute, hour and day components as numeric vectors.

`new_hms()` is a low-level constructor that only checks that its input has the correct base type, [numeric](#).

`is_hms()` checks if an object is of class `hms`.

`as_hms()` is a generic that supports conversions beyond casting. The default method forwards to [vec_cast\(\)](#).

Usage

```
hms(seconds = NULL, minutes = NULL, hours = NULL, days = NULL)
```

```
new_hms(x = numeric())
```

```
is_hms(x)
```

```
as_hms(x, ...)
```

```
## S3 method for class 'hms'
as.POSIXct(x, ...)
```

```
## S3 method for class 'hms'
as.POSIXlt(x, ...)
```

```
## S3 method for class 'hms'
as.character(x, ...)
```

```
## S3 method for class 'hms'
format(x, ...)
```

```
## S3 method for class 'hms'
print(x, ...)
```

```
## S3 method for class 'hms'
seq(from = hms(1), to = hms(1), by = NULL, ...)
```

Arguments

seconds, minutes, hours, days	Time since midnight. No bounds checking is performed.
x	An object.
...	additional arguments to be passed to or from methods.
from, to	the starting and (maximal) end values of the sequence. Of length 1 unless just from is supplied as an unnamed argument.
by	number: increment of the sequence.

Details

For `hms()`, all arguments must have the same length or be `NULL`. Odd combinations (e.g., passing only seconds and hours but not minutes) are rejected.

For arguments of type `POSIXct` and `POSIXlt`, `as_hms()` does not perform timezone conversion. Use `lubridate::with_tz()` and `lubridate::force_tz()` as necessary.

Examples

```
hms(56, 34, 12)
hms()

new_hms(as.numeric(1:3))
# Supports numeric only!
try(new_hms(1:3))

as_hms(1)
as_hms("12:34:56")
as_hms(Sys.time())
as.POSIXct(hms(1))
data.frame(a = hms(1))
d <- data.frame(hours = 1:3)
d$hours <- hms(hours = d$hours)
d
```

 parse_hms

Parsing hms values

Description

These functions convert character vectors to objects of the `hms` class. NA values are supported.

`parse_hms()` accepts values of the form "HH:MM:SS", with optional fractional seconds.

`parse_hm()` accepts values of the form "HH:MM".

Usage

```
parse_hms(x)
```

```
parse_hm(x)
```

Arguments

x A character vector

Value

An object of class [hms](#).

Examples

```
parse_hms("12:34:56")
parse_hms("12:34:56.789")
parse_hm("12:34")
```

round_hms	<i>Round an hms object</i>
-----------	----------------------------

Description

Convenience functions to round to a multiple of seconds or digits.

Usage

```
round_hms(x, secs = NULL, digits = NULL)

trunc_hms(x, secs = NULL, digits = NULL)

ceiling_hms(x, secs = NULL, digits = NULL)

floor_hms(x, secs = NULL, digits = NULL)
```

Arguments

x A vector of class [hms](#)

secs Multiple of seconds, a positive numeric. Values less than one are supported

digits Number of digits, a whole number. Negative numbers are supported.

Value

The input, rounded or truncated to the nearest multiple of secs (or number of digits)

Examples

```

round_hms(as_hms("12:34:56"), 5)
round_hms(as_hms("12:34:56"), 60)
round_hms(as_hms("12:34:56.78"), 0.25)
round_hms(as_hms("12:34:56.78"), digits = 1)
round_hms(as_hms("12:34:56.78"), digits = -2)
trunc_hms(as_hms("12:34:56"), 60)
ceiling_hms(as_hms("12:34:56"), 60)
floor_hms(as_hms("12:34:56"), 60)

```

vec_cast.hms

*Casting***Description**

Double dispatch methods to support `vecr::vec_cast()`.

Usage

```

## S3 method for class 'hms'
vec_cast(x, to, ...)

```

Arguments

x	Vectors to cast.
to	Type to cast to. If NULL, x will be returned as is.
...	For <code>vec_cast_common()</code> , vectors to cast. For <code>vec_cast()</code> , <code>vec_cast_default()</code> , and <code>vec_restore()</code> , these dots are only for future extensions and should be empty.

vec_ptype2.hms

*Coercion***Description**

Double dispatch methods to support `vecr::vec_ptype2()`.

Usage

```

## S3 method for class 'hms'
vec_ptype2(x, y, ..., x_arg = "", y_arg = "")

```

Arguments

x, y	Vector types.
...	These dots are for future extensions and must be empty.
x_arg, y_arg	Argument names for x and y. These are used in error messages to inform the user about the locations of incompatible types (see stop_incompatible_type()).

Index

`as.character.hms (hms)`, 2
`as.POSIXct.hms (hms)`, 2
`as.POSIXlt.hms (hms)`, 2
`as_hms (hms)`, 2

`ceiling_hms (round_hms)`, 4

`difftime`, 2

`floor_hms (round_hms)`, 4
`format.hms (hms)`, 2

`hms`, 2, 3, 4

`is_hms (hms)`, 2

`lubridate::force_tz()`, 3
`lubridate::with_tz()`, 3

`new_hms (hms)`, 2
`numeric`, 2

`parse_hm (parse_hms)`, 3
`parse_hms`, 3
`POSIXct`, 3
`POSIXlt`, 3
`print.hms (hms)`, 2

`round_hms`, 4

`seq.hms (hms)`, 2
`stop_incompatible_type()`, 6

`trunc_hms (round_hms)`, 4

`vctrs::vec_cast()`, 5
`vctrs::vec_ptype2()`, 5
`vec_cast()`, 2
`vec_cast.hms`, 5
`vec_ptype2.hms`, 5